



BAJUTSU SHL-G406

Product Description:

Bajutsu Fully Synthetic n advanced full synthetic 0W-16. It's our strongest oil and formulated to withstand the extreme pressure and temperatures. It's the best option for those who want to push their car to its limits. It oil address emerging engine technology as vehicle manufacturers strive to optimize fuel economy. Honda, Lexus and Toyota recommend 0W-16 oils for select gasoline and hybrid engines beginning with the 2018 model year.

Applications / Benefits:

Exceptional wear protection for engine reliability
Cleanliness control to maintain engine drivability.
Freedom from LSPI to prolong engine life
Optimised oxidation and deposit control
Strong Fuel Economy Improvement

Specifications, Approvals & Recommendations

API SP-RC
ILSAC GF-6B

Typical Physical Characteristics

Test Description	Method	G406
SAE Viscosity Grade	SAE J 300	0W-16
Specific Gravity @15°C	ASTM D 4052	0.831
Flash Point, °C	ASTM D 92	216
Pour Point, °C	ASTM D 97	-42
Kinematic Viscosity @40°C cSt	ASTM D 445	36.1
Kinematic Viscosity @100°C cSt	ASTM D 445	7.30
Viscosity Index	ASTM D 2270	172
TBN, mgKOH/g	ASTM D 2896	7.0
Color	ASTM D 1500	<3.0
CCS, cP	ASTM D 5293	5329
HTHS, Cp	ASTM D 5481	2.36

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.
Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.