



BAJUTSU SHL-G409, G410, G411

Product Description:

Bajutsu Fully Synthetic oil is Premium Tier Full SAPS Additive Technology Fulfilling ACEA A3/B4, API SP and OEM Requirements. It delivers excellent wear protection and antioxidant performance, as well as lowspeed pre-ignition (LSPI) protection. It provides robust operation for your vehicle and supports a longer vehicle life. They are designed for a use in high performance gasoline and light duty diesel engines and are typically used in newer vehicles as they provide the minimum performance demanded by many OEM specifications.

Applications / Benefits:

Outstanding oxidation performance
Sludge Handling
Robust LSPI prevention and wear protection
Tailored sludge and varnish control

Specifications, Approvals & Recommendations

API SP
ACEA A3/B4
MB 229.3
MB 229.5 */**
MB 226.5
VW 501.00 / 505.00 ***
VW 502.00 / 505.00 */**
Renault RN 0710 / 0700
Fiat M2 **
PSA B71 2300 ***

*Please note official claim apply to SAE 5W30, only

**Please note official claim apply to SAE 5W40, only

***Please note official claim apply to SAE 10W40, only

Typical Physical Characteristics

Test Description	Method	G409	G410	G411
SAE Viscosity Grade	SAE J 300	5W-30	5W-40	10W-40
Specific Gravity @ 15 °C	ASTM D 4052	0.858	0.861	0.862
Flash Point, °C	ASTM D 92	212	220	220
Pour Point, °C	ASTM D 97	-39	-39	-36
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	70.1	88.9	100.4
cSt @ 100°C	ASTM D 445	11.80	14.50	15.10
Viscosity Index	ASTM D 2270	165	170	158
TBN, mgKOH/g	ASTM D 2896	11.0	11.0	11.0
Color	ASTM D 1500	<3.5	<3.5	<3.5
CCS, cP	ASTM D 5293	≤6600	≤6600	≤7000
HTHS, cP	ASTM D 5481	≥3.5	≥3.5	≥3.5

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinloub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.