



BAJUTSU SHL- G413, G414

Product Description:

Bajutsu Fully Synthetic oil engine oil additive is specially designed for use in catalyst compatible oils. These particular oils are used in light duty vehicles fitted with after-treatment systems, gasoline catalytic converter and diesel particulate filter technology.

Applications / Benefits:

- Outstanding oxidation performance
- Sludge Handling
- Robust LSPI prevention and wear protection
- Tailored sludge and varnish control

Specifications, Approvals & Recommendations

ACEA C3
API SP
MB 229.31

Typical Physical Characteristics

Properties	Method	G413	G414
SAE Viscosity Grade	SAE J 300	5W30	5W40
Specific Gravity @15°C	ASTM D 4052	0.850	0.855
Flash Point @°C	ASTM D 92	214	216
Pour Point @°C	ASTM D 97	-39	-39
Kinematic Viscosity @40°C cSt	ASTM D 445	70.1	91.9
Kinematic Viscosity @100°C cSt	ASTM D 445	11.8	14.5
Viscosity Index	ASTM D 2270	165	164
TBN, mgKOH/g	ASTM D 2896	7.8	7.8
Color	ASTM D 1500	<2.5	<2.5
CCS, cP	ASTM D 5293	5215	5536

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.