



BAJUTSU SHL- G415

Product Description:

Bajutsu Fully Synthetic oil engine oil a top-tier mid-SAPS additive solution for European engine oils that is designed to meet the increasing demands of the latest and future generation gasoline and diesel engines. Ability to protect both diesel and gasoline particulate filters ensures you can target a high-value market.

Applications / Benefits:

Improved fuel efficiency
An advanced future proofed Mid SAPS technology
DPF & GPF compatibility
LSPI Protection
Superior differentiating OEM Performance

Specifications, Approvals & Recommendations

API SP
ACEA C3
BMW LL-04
MB 229.51
MB 229.52
PORCHE C30
VW 504/507
Opel OV 040 1547

Typical Physical Characteristics

Test Description	Units	ASTM Method	SHL- G415
SAE Viscosity Grade		-	5W-30
Appearance	-	Visual	B & C
Color	-	D 1500	<3.5
Density @15°C	kg/l	D 4052	0.8437
Kinematic Viscosity	@-40°C cSt	D 445	68.36
	@100°C cSt	D 445	11.94
Viscosity Index	-	D 2270	173
Total Base Number	mgKOH/g	D 2896	8
Flash Point COC	°C	D 92	220
Pour Point	°C	D 97	-39

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.