



NINJUTSU SHL-T303

Product Description:

NINJUTSU ATF Multi-Vehicle is a premium Synthetic lubricant formulated from selected high-quality synthetic base oils combined with an advanced additive system designed to meet the service fill needs of the broadest range of step-type automatic transmissions in vehicles from European, American and Asian car builders.

NINJUTSU ATF Multi-Vehicle provides protection against wear and provides the required friction rate to transfer high torque. Increased stability to physical fluid deterioration and oxidation to allow the retention of initial performance in extended service intervals.

Applications / Benefits:

Backward compatibility
Extended drain intervals
Maximum transmission life
Multipurpose application
Smoother shift feels

Specifications, Approvals & Recommendations

AISIN	JWS 3309 ATF, ATF-OT4
AISIN	JWS 3324 ATF, ATF-OWS
ALLISON	C2, C3, C4
ATF	134, 3100 PL085, 3353, 3403-M115
ATF	DX-VI, ETL-7045 E, K17
ATF	L12108, LA 2634
ATF	M-1375.4, M-1375.6
ATF	N402, SP-III
BENTLEY	P/N PY112995PA
BMW	ATF 3+, ATF 4, ATF 6
BMW	ETL-7045, ETL-7045 E, ETL-8072B
BMW	LA 2634, LT 71141, M-L12108
BMW	P/N 81 22 9 400 272, P/N 81 22 9 400 275, P/N 81 22 9 407 858, P/N 81 22 9 407 859
BMW	P/N 83 22 0 024 249, P/N 83 22 0 024 359, P/N 83 22 0 026 922, P/N 83 22 0 142 516
BMW	P/N 83 22 0 397 114, P/N 83 22 0 402 413, P/N 83 22 0 403 248, P/N 83 22 0 403 249
BMW	P/N 83 22 2 152 426, P/N 83 22 2 163 514, P/N 83 22 2 220 438, P/N 83 22 2 220 440
BMW	P/N 83 22 2 220 442, P/N 83 22 2 289 720, P/N 83 22 2 305 396, P/N 83 22 2 305 397
BMW	P/N 83 22 2 355 599, P/N 83 22 2 355 601, P/N 83 22 7 542 290, P/N 83 22 9 407 765
BMW	P/N 83 22 9 407 807
BOSCH	BOSCH TE-ML 09
CITROEN	Z 000169756
DAIHATSU	D3-SP
FCA	8 & 9 SPEED ATF, P/N 68218925AA/AB
FCA	ASRC, ATF+, ATF+2, ATF+3, ATF+4
FCA	AW-1, P/N 68092912AA, DEX-VI, P/N 68043742AA
FCA	FIAT 9.55550-AV1, FIAT 9.55550-AV2, FIAT 9.55550-AV4
FCA	FIAT 9.55550-AV5, FIAT 9.55550-AV6
FCA	MB 236.10/12, P/N 05127382AA
FCA	P/N 05127382, P/N 68157995AA/AB, P/N 68333587AA
FCA	SP-4, P/N 68171866AA, SP-III
FCA	SP-IV, P/N 68171866AA, SP-IV, P/N 68171869AA
FCA	TYPE 7176E, TYPE 9602
FORD	ESP-M2C138-CJ, ESP-M2C166-H
FORD	P/N XT-10-QLV [LV], P/N XT-2-QDX [M]
FORD	P/N XT-2-QSM [SYN], P/N XT-5-QM [V]
FORD	P/N XT-5-QSM [V SYN], P/N XT-6-QSP [SP]



P
R
O
D
U
C
T

D
A
T
A

S
H
E
E
T

FORD	P/N XT-8-QAW [PREMIUM], P/N XT-9-QMM5 [FRN5]
FORD	WSS-M2C922-A1
GM	ATF Z1, SATURN P/N 22717466, AW1, P/N 19256039
GM	DEX [6032M], DEX HP [GMW 16974], DEX-B [6032M]
GM	DEX-IIC [6137M], DEX-IID [GM 6137M]
GM	DEX-IIIE [GM 6137M], DEX-IIIF [GM 6297M]
GM	DEX-IIIG [GM 6417M], DEX-IIIH [GM N10055]
GM	P/N 19 40 700, P/N 19 40 767
GM	P/N 21005966, P/N 88900925
GM	P/N 9985010, P/N 9986195
GM	SATURN T-IV Fluid SATURN P/N 22689186
GM	TYPE A SUFFIX A
GM	WS, P/N 88863400, WS, P/N 88863401
HONDA / ACURA	ATF DW-1 P/N 08200-9008)
HONDA / ACURA	ATF Type 3.0 P/N 08200-9016-A, ATF Type 3.1 P/N 08200-9017
HONDA / ACURA	ATF Z1, P/N 08200-9001, ATF Z1, P/N 08200-9001A
HYUNDAI / KIA	ATF RED-1K, ATF SP-IV, GENUINE ATF, JWS 3314
HYUNDAI / KIA	P/N 00232-19023, P/N 040000C90SG
HYUNDAI / KIA	P/N 04500-00140, P/N UM040 CH20 Red-1
HYUNDAI / KIA	SP, SP4-M1, SPH-IV, SPH-IV-RR
HYUNDAI / KIA	SP-II, SP-III, SP-IV, SP-IV-RR
HYUNDAI / KIA	WS, SPEC NWS-9638
ISUZU	ATF II, ATF III, ATF WSI
ISUZU	GENUINE ATF, P/N 08200-9001, SCS
JAGUAR	02JDE 26444, FLUID 8432,
JAGUAR	JLM 20238, JLM 20292, JLM 21044
JAGUAR	K17, JATCO 3100 PL085, LT 71141
JAGUAR	WSS-M2C922-A1
JAMA	ASO M315, Class 1-A
JAMA	ASO M315, Class 1-A-LV
LAND ROVER	ATF N402, AW-1 P/N LR0022460: LV
LAND ROVER	JWS 3309US, P/N TYK500050
LAND ROVER	LR 023288, LR 023289
LAND ROVER	P/N TYK500050
MAN	339A, 339D, 339F
MASERATI	OIL NO. 231603
MAZDA	ATF FZ, ATF M-5 P/N 0000-23-ATF -M5
MAZDA	ATF N-1, ATF S-1
MAZDA	F-1, JWS3317, M3
MAZDA	TYPE T-IV, JWS 3309 ATF
MERCEDES	A 0019892203, ATF 3403-M115,
MERCEDES	MB 236.1, MB 236.10, MB 236.11
MERCEDES	MB 236.12, MB 236.14, MB 236.15
MERCEDES	MB 236.2, MB 236.41, MB 236.5
MINI	ATF JWS 3309, P/N 83 22 0 402 413
MITSUBISHI	ATF-J2, ATF-J3
MITSUBISHI	DIA QUEEN ATF-MA1, P/N MZ320775
MITSUBISHI	DIA QUEEN ATF-PA, P/N 4030401
MITSUBISHI	DIA QUEEN AW, DII, DIII
MITSUBISHI	SP, P/N MS991156
MITSUBISHI	SP-II, SP-III, SP-IV
NISSAN	FLUID A, MATIC D
NISSAN	MATIC J, P/N 999MP-MTJ00P
NISSAN	MATIC K
NISSAN	MATIC R, P/N 999MP-MTR00P
NISSAN	MATIC S, P/N 999MP-MTS00P
NISSAN	MATIC W, N402



PRODUCT

DATA

SHEET

PEUGEOT	P/N Z 000169756
PORSCHE	JWS 3309, P/N 000 043 205 28
PORSCHE	LT 71141
PORSCHE	P/N 000 043 204 41, P/N 000 043 204 63
PORSCHE	P/N 000 043 304 00, P/N 000 043 304 01
PORSCHE	P/N 000 043 305 42, P/N 000 043 305 43
PORSCHE	P/N 000 043 305 54, P/N 000 043 306 24
PORSCHE	P/N 958 300 540 00, P/N 958 300 901 00
PORSCHE	P/N 999 917 547 00 (A2), P/N 000 043 205 09
PSA	AL4 / 4HP20, P/N 9730AE
PSA	B71 2340
RENAULT	DP-0, MATIC D2, SATF-D
ROLLS ROYCE	OIL NO. PL 31493PA
SAAB	ATF HP, JWS 3309
SAAB	P/N 93 160 393, P/N 93 165 147
SATURN	DEX-IIG,
SATURN	T-IV FLUID , P/N 22689186
SSANGYONG	DSIH 5M-52, DSIH 5M-66
SUBARU	ATF HP P/N K0140Y0700, ATF HP P/N SOA635040
SUBARU	ATF-WS
SUZUKI	ATF 2326, ATF 2384K, ATF 3314
SUZUKI	ATF 3317, ATF 5D06
SUZUKI	MATIC D, MATIC J, MATIC S
TOYOTA	ATF FZ
TOYOTA	JWS 3309, Type T-IV, P/N 08886-81015
TOYOTA	JWS 3324, ATF WS (or NWS9638)
TOYOTA	TYPE D-II, TYPE T
TOYOTA	TYPE T-II, TYPE T-III
VOLVO	P/N 1161521, P/N 1161621, P/N 1161640
VOLVO	P/N 1161540, P/N 31 256 774, 31 256 775
VOLKSWAGEN / AUDI	G 052 162 (-A1, -A2) [AG4]
VOLKSWAGEN / AUDI	G 052 533, G 052 990 A2, G 055 005 A2
VOLKSWAGEN / AUDI	G 055 025 (-A2), G 055 162 A2 or A6
VOLKSWAGEN / AUDI	G 055 540 A2, G 060 162 A2, G US 000 162
VOLKSWAGEN / AUDI	LT 71141
ZF	LIFEGUARDFLUID 5 (ZF No. S671 090 170)
ZF	LIFEGUARDFLUID 6 (ZF No. S671 090 255)
ZF	LIFEGUARDFLUID 8 (ZF No. S671 090 312)
ZF	LIFEGUARDFLUID 9 (ZF No. AA01.500.001)
ZF	TE-ML 11A, TE-ML 11B

Typical Physical Characteristics

Test Description	Method	SHL-T303
Density @15°C	ASTM D4052	0.845
Kinematic Viscosity @40°C cSt	ASTM D445	26.72
Kinematic Viscosity @100°C cSt	ASTM D445	5.66
Viscosity Index	ASTM D2270	160
Flash point, °C	ASTM D92	198
Pour Point, °C	ASTM D97	-45

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.