



NINJUTSU SHL-T305

Product Description:

NINJUTSU ATF WS is a synthetic low viscosity fluid for automatic transmission with or without slip controlled lock-up clutch system.

NINJUTSU ATF WS provides full protection to all parts of the transmission system and guarantees a reliable performance even in high loads. Superior automatic transmission response and smoother gear shifts. It meets the requirements of all AISIN-WARNER automatic transmission in Japanese, American, European and other OEMs requiring a WS fluid. Aisin type WS ("World Standard") fluid is the factory fill ATF for modern 6- and 8-speed Aisin-Warner automatic transmissions

Applications / Benefits:

- Fuel economy
- Optimized drain intervals
- Superior anti-wear protection
- Superior friction performance
- Superior oxidation control

Specifications, Approvals & Recommendations

TOYOTA ATF WS
LEXUS JWS 3309

Typical Physical Characteristics

Test Description	Method	SHL-T305
Specific Gravity @15°C	ASTM D4052	0.845
Kinematic Viscosity @40°C cSt	ASTM D445	26.72
Kinematic Viscosity @100°C cSt	ASTM D445	5.66
Viscosity Index	ASTM D2270	160
Flash point, °C	ASTM D92	198
Pour Point, °C	ASTM D97	-45
Appearance	Visual	Red

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.