



NINJUTSU SHL-T306

Product Description:

NINJUTSU ATF T-IV is a synthetic automatic transmission fluid specially engineered to exceed the service fill requirement of all TOYOTA and LEXUS vehicles installed with AISIN WARNER gearboxes, where ATF T-IV fluid is recommended.

NINJUTSU ATF T-IV (Type 4 transmission fluid) can be used in all automatic transmissions that require ATF T, T2, T3 or T4. Do not use this fluid if your manual states your transmission uses Dexron or ATF WS.

Applications / Benefits:

Extended protection
Optimized drain intervals
Superior anti-wear protection
Transmission cleanliness

Specifications, Approvals & Recommendations

TOYOTA ATF T-IV

Typical Physical Characteristics

Test Description	Method	SHL-T306
Specific Gravity @15°C	ASTM D4052	0.853
Kinematic Viscosity @40°C cSt	ASTM D445	38.1
Kinematic Viscosity @100°C cSt	ASTM D445	7.24
Viscosity Index	ASTM D2270	157
Flash point, °C	ASTM D92	198
Pour Point, °C	ASTM D97	-45
Appearance	Visual	Red

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.