



P  
R  
O  
D  
U  
C  
T

## NINJUTSU SHL-T308

### Product Description:

NINJUTSU ATF SP-III is a synthetic automatic transmission fluid specially engineered to exceed the service fill requirement of all MITSUBISHI, HYUNDAI and KIA vehicles equipped with 4-5 speed automatic transmission systems, where SP III fluid is required. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy. It is designed on the basis of the requirements set by Korean car manufacturers.

### Applications / Benefits:

Extended protection  
Optimized drain intervals  
Superior anti-wear protection  
Transmission cleanliness

### Specifications, Approvals & Recommendations

MITSUBISHI ATF SP III  
HYUNDAI SP-III  
KIA SP-III

D  
A  
T  
A

### Typical Physical Characteristics

| Test Description               | Method     | SHL-T308 |
|--------------------------------|------------|----------|
| Specific Gravity @15°C         | ASTM D4052 | 0.853    |
| Kinematic Viscosity @40°C cSt  | ASTM D445  | 38.1     |
| Kinematic Viscosity @100°C cSt | ASTM D445  | 7.24     |
| Viscosity Index                | ASTM D2270 | 157      |
| Flash point, °C                | ASTM D92   | 198      |
| Pour Point, °C                 | ASTM D97   | -45      |
| Appearance                     | Visual     | Red      |

S  
H  
E  
E  
T

### Health, Safety & Environment

#### Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.  
Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.  
Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

#### Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.