



NINJUTSU SHL-T309

Product Description:

NINJUTSU ATF DW-1 is a synthetic automatic transmission fluid formulated to provides hydraulic power to maintains optimum shift quality over a long period of use. ATF DW-1 has lower viscosity which translates into better gas mileage, and the lubricating properties have been improved. ATF DW-1 can lubricates and cools internal components.

Applications / Benefits:

Fuel economy
Optimized drain intervals
Superior anti-wear protection
Superior friction performance
Superior oxidation control

Specifications, Approvals & Recommendations

ATF DW-1

Typical Physical Characteristics

Test Description	Method	T309
Specific Gravity @15°C	ASTM D 4052	0.8530
Flash point, °C	ASTM D 92	192
Pour Point, °C	ASTM D 97	-45
Kinematic Viscosity, @40°C cSt	ASTM D 445	25.2
@100°C cSt	ASTM D 445	6.99
Viscosity Index	ASTM D 2270	264
Appearance	Visual	Red

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.