



NINJUTSU SHL-T312

Product Description:

NINJUTSU CVT TC is a synthetic transmission fluid that is specifically formulated to meet the demanding performance requirements of conventional Toyota CVT systems. It is designed to provide excellent protection against wear, corrosion, and foaming, as well as to help ensure the smooth and efficient operation of the transmission.

CVT TC was launched together with the first Toyota/Aisin CVT, the first special fluid for CVT transmission was introduced in 2000.

Applications / Benefits:

Improved fuel economy and Reduced emissions

Improved resistance to oxidation, thermal breakdown and oil sludge

Reduced oil waste through less frequent oil changes

Specifications, Approvals & Recommendations

TOYOTA CVT TC

Typical Physical Characteristics

Test Description			Method	T312
Specific Gravity	@15°C		ASTM D 4052	0.849
Flash point,	°C		ASTM D 92	198
Pour Point,	°C		ASTM D 97	-45
Kinematic Viscosity,	@40°C	cSt	ASTM D 445	30.14
	@100°C	cSt	ASTM D 445	6.88
Viscosity Index			ASTM D 2270	200
Viscosity, brookfield	@40°C	mPa.s	ASTM D 2983	13260.0
Appearance			Visual	Red

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.