



NINJUTSU SHL-T313

Product Description:

NINJUTSU CVTF NS-3 is a high performance synthetic automatic transmission fluid formulated to meet the demanding requirements of modern Asian, American, European vehicles equipped with continuously variable transmissions (CVT), including chain-CVT and belt-CVT designs.

Unique formulation of high quality friction modifiers and additives ensures stable, precise operation. Offers superior low temperature fluidity for smoother shifting and maintains proper pressure in hot weather. For use in Nissan models with CVT gearbox. Improve the performance and longevity of your Nissan vehicle.

Applications / Benefits:

- Prolongs transmission life
- Extended drain intervals
- Fuel efficiency
- Optimum driving comfort

Specifications, Approvals & Recommendations

NISSAN CVT NS-3
INFINITI NS-3

Typical Physical Characteristics

Test Description	Method	SHL-T313
Specific Gravity @15°C	ASTM D4052	0.852
Kinematic Viscosity @40°C cSt	ASTM D445	28.14
Kinematic Viscosity @100°C cSt	ASTM D445	5.83
Viscosity Index	ASTM D2270	157
Viscosity, Brookfield @40°C mPa.s	ASTM D 2983	11230
Flash point, °C	ASTM D92	198
Pour Point, °C	ASTM D97	-45
Appearance	Visual	Green

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.