



P
R
O
D
U
C
T

NINJUTSU SHL-T314

Product Description:

NINJUTSU CVTF NS-2 is a high performance synthetic automatic transmission fluid formulated to meet the demanding requirements of modern Asian, American, European vehicles equipped with continuously variable transmissions (CVT), including

Unique formulation of high quality friction modifiers and additives ensures stable, precise operation. Offers superior low temperature fluidity for smoother shifting and maintains proper pressure in hot weather. For use in Nissan models with CVT gearbox. Improve the performance and longevity of your Nissan vehicle.

Applications / Benefits:

Prolongs transmission life
Extended drain intervals
Fuel efficiency
Low oxidation rate for improved long-term stability

Specifications, Approvals & Recommendations

NISSAN CVT NS-2

Typical Physical Characteristics

Test Description	Method	T314
Specific Gravity @15°C	ASTM D 4052	0.852
Flash point, °C	ASTM D 92	198
Pour Point, °C	ASTM D 97	-45
Kinematic Viscosity, @40°C cSt	ASTM D 445	32.2
@100°C cSt	ASTM D 445	7.2
Viscosity Index	ASTM D 2270	198
Viscosity, brookfield @40°C mPa.s	ASTM D 2983	11260
Appearance	Visual	Green

D
A
T
A

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap. Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

S
H
E
E
T