



P
R
O
D
U
C
T

NINJUTSU SHL-T315

Product Description:

NINJUTSU CVT HCF-2 is a synthetic transmission fluid that is specifically formulated for multi-OEM's chain and push belt type CVT. This transmission can keep the engine's speed within the most efficient range. Furthermore, CVT HCF-2 can guarantee a high viscosity index, excellent protection against high pressure, friction and wear and optimal power transmission.

Applications / Benefits:

Longer drain periods
Effective foam control
Maintains proper pressure in hot weather
Smoother low temperature shifting
Superior anti-wear protection

Specifications, Approvals & Recommendations

CVT HCF-2

Typical Physical Characteristics

Test Description			Method	T315
Specific Gravity	@15°C		ASTM D 4052	0.850
Flash point,	°C		ASTM D 92	174
Pour Point,	°C		ASTM D 97	-45
Kinematic Viscosity,	@40°C	cSt	ASTM D 445	25.75
	@100°C	cSt	ASTM D 445	7.06
Viscosity Index			ASTM D 2270	260
Color			ASTM D 1500	<2.0

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

D
A
T
A

S
H
E
E
T