



P
R
O
D
U
C
T

NINJUTSU SHL-T316

Product Description:

NINJUTSU CVT HMMF is a synthetic transmission fluid that is specifically formulated for continuously variable transmissions (CVT) to ensure reliable operation and outstanding fluidity at low temperatures. This fluid can provide system CVT based on the method of starting the clutch in cars HONDA, and has a longer life.

Applications / Benefits:

Prolongs transmission life
Extended drain intervals
Fuel efficiency
Low oxidation rate for improved long-term stability

Specifications, Approvals & Recommendations

CVT HMMF

Typical Physical Characteristics

Test Description			Method	T316
Specific Gravity	@15°C		ASTM D 4052	0.852
Flash point,	°C		ASTM D 92	198
Pour Point,	°C		ASTM D 97	-45
Kinematic Viscosity,	@40°C	cSt	ASTM D 445	30
	@100°C	cSt	ASTM D 445	7.5
Viscosity Index			ASTM D 2270	234
Viscosity, Brookfield	@40°C	mPa.s	ASTM D 2983	11260
Appearance			Visual	Light Red

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

D
A
T
A

S
H
E
E
T