



BAJUTSU SHL- G202, G203, G204

Product Description:

Bajutsu Premium Mineral is an API SP certified premium quality multi-grade motor oil designed for maximum engine protection and exceptional fuel economy even under extreme driving conditions. Technologically advanced additive system reduces friction and wear at start-up, and protects your engine against performance robbing sludge and varnish deposits.

Bajutsu Premium Mineral Engine Oil uses a specialized formula for older, high mileage engines, which delivers outstanding antiwear performance and helps reduce oil consumption and leakage.

Applications / Benefits:

- Extended engine life
- High viscosity index
- Low oil consumption and turbo proven stability

Specifications, Approvals & Recommendations

API SP
API SN SM, SL, SJ and previous passenger car service

Typical Physical Characteristics

Test Description	Method	G202	G203	G204
SAE Viscosity Grade	SAE J 300	10W-40	15W-40	20W-50
Specific Gravity @ 15 °C	ASTM D 4052	0.877	0.878	0.882
Flash Point, °C	ASTM D 92	216	220	240
Pour Point , °C	ASTM D 97	-30	-27	-21
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	96.1	113.1	175.3
cSt @ 100°C	ASTM D 445	14.60	14.90	19.50
Viscosity Index	ASTM D 2270	158	136	128
TBN, mgKOH/g	ASTM D 2896	7.0	7.0	7.0
Color	ASTM D 1500	<3.0	<3.0	<3.0

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.