



NINJUTSU SHL- G205, G206, G207, G208, G209

Product Description:

Bajutsu Premium Mineral is a versatile cascade additive package, efficiently designed for passenger car, light duty diesel & 4-strokes motorcycle engine oil applications. This “all-in-one” solution is ideal for oil marketers who produce engine oils for different vehicle types, making production even simpler!

Applications / Benefits:

Active Cleaning Agents
Excellent oxidation resistance and stability at high temperatures
Outstanding wear control
Low oil consumption and turbo proven stability

Specifications, Approvals & Recommendations

API SL/CF
JASO MA

Typical Physical Characteristics

Test Description	Method	G205	G206	G207	G208	G209
SAE Viscosity Grade	SAE J 300	10W-30	10W-40	15W-40	15W-50	20W-50
Specific Gravity @15°C	ASTM D 4052	0.878	0.882	0.886	0.885	0.893
Flash point, °C	ASTM D 92	212	215	220	224	235
Pour Point, °C	ASTM D 97	-30	-27	-24	-24	-18
Kinematic Viscosity, @40°C cSt	ASTM D 445	78.1	102	109	145	175
@100°C cSt	ASTM D 445	11.8	14.9	15	18.9	19.5
Viscosity Index	ASTM D 2270	145	152	143	148	128
TBN, mgKOH/g	ASTM D 2896	6.1	6.1	6.1	6.1	6.1
Color	ASTM D 1500	2.5	2.5	2.5	2.5	2.5
CCS, cP	ASTM D 5293	≤7000	≤7000	≤7000	≤7000	≤9500
HTHS, cP	ASTM D 5481	≥2.9	≥3.5	≥3.7	≥3.7	≥3.7

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.