



NINJUTSU SHL-T301

Product Description:

NINJUTSU premium automatic transmission long life fluid based on an advanced synthetic technology allowing very high performance needed for the demanding requirements of the 10 speed transmission designs. This new transmission offers great efficiency, and performance, while also optimizing fuel economy.

The 10-speed delivers improved overall performance, with enhanced acceleration at the low and mid ranges of the power band. Features include optimized wide-span gear spacing coupled with drag-reduction actions plus three overdrive gears.

Applications / Benefits:

- Backward compatibility
- Extended drain intervals
- Maximum transmission life
- Multipurpose application
- Smoother shift feels

Specifications, Approvals & Recommendations

Dexron ULV
Mercon ULV
Ford 10R60 / 10R80
GM 10L80 / 10L90

Typical Physical Characteristics

Test Description	Method	SHL-T301
Appearance	Visual	Red
Density @15°C	ASTM D4052	0.845
Kinematic Viscosity @40°C cSt	ASTM D445	19.2
Kinematic Viscosity @100°C cSt	ASTM D445	4.55
Viscosity Index	ASTM D2270	160
Viscosity, Brookfield @ -40°C mPa.s	ASTM D 2983	4270
Flash point, °C	ASTM D92	198
Pour Point, °C	ASTM D97	-45

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.