

SOJUTSU SHL- M201,M202,M203,M204,M205,M206

Product Description:

Sojutsu Premium Mineral is a high-quality motorcycle oil most suited for four-stroke motorcycles equipped with either wet or dry clutch systems. It provides engines with reliable protection and effective cleaning action for dependable performance under continuous and heavy-duty driving conditions.

This is a lubricating mineral oil for general use in low-specification fourstroke engines. It is suitable for a wide range of motorcycles and is recommended for urban use. It also withstands the very high temperatures produced by intensive use in urban traffic.

Applications / Benefits:

Excellent wear, cleanliness and corrosion protection

Excellent shear stability to prevent viscosity breakdown

Long engine life

Maintains viscosity of the oil at high temperature to prevent engine wear

Specifications, Approvals & Recommendations

API SL

JASO MA/MA2

Typical Physical Characteristics

Test Description	Unit	Method	SHL- M201	SHL- M202	SHL- M203
SAE Viscosity Grade		SAE J 300	10W-30	10W-40	15W-40
Specific Gravity	@15°C	ASTM D 4052	0.878	0.882	0.886
Flash Point	°C	ASTM D 92	212	215	220
Pour Point	°C	ASTM D 97	-30	-27	-24
Kinematic Viscosity	@40°C cSt	ASTM D 445	78.1	102	109
	@100°C cSt	ASTM D 445	11.8	14.9	15
Viscosity Index	-	ASTM D 2270	145	152	143
Total Base Number	mgKOH/g	ASTM D 2896	6.1	6.1	6.1
Color		ASTM D 1500	<3.0	<3.0	<3.0

Test Description	Unit	Method	SHL- M204	SHL- M205	SHL- M206
SAE Viscosity Grade		SAE J 300	15W-50	20W-40	20W-50
Specific Gravity	@15°C	ASTM D 4052	0.885	0.880	0.893
Flash Point	°C	ASTM D 92	224	234	235
Pour Point	°C	ASTM D 97	-24	-18	-18
Kinematic Viscosity	@40°C cSt	ASTM D 445	145	135.4	175
	@100°C cSt	ASTM D 445	18.9	15.3	19.5
Viscosity Index	-	ASTM D 2270	148	116	128
Total Base Number	mgKOH/g	ASTM D 2896	6.1	6.1	6.1
Color		ASTM D 1500	<3.0	<3.0	<3.0

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.