



SOJUTSHU SHL- M404

Product Description:

Sojutsu Fully Synthetic lubricant is perfect for four-stroke engines. It provides high thermal stability and its viscosity grade facilitates engine start-up at all temperatures. This makes Sojutsu 4T perfect for motorcycles which are parked on the street overnight or are driven in places with a changeable climate. It helps keep four-stroke engines running clean, providing protection even in extreme operating conditions.

Applications / Benefits:

Cleans and protects
Emissions Conformity
Oxidation Stability
Power and Control
Reduces engine heat damage

Specifications, Approvals & Recommendations

API SP

JASO MA/MA2

Typical Physical Characteristics

Test Description	Unit	Method	SHL- M404
SAE Viscosity Grade		SAE J 300	5W-50
Specific Gravity	@15°C	ASTM D 4052	0.857
Flash Point	°C	ASTM D 92	222
Pour Point	°C	ASTM D 97	-39
Kinematic Viscosity	@40°C cSt	ASTM D 445	119.3
	@100°C cSt	ASTM D 445	18.5
Viscosity Index	-	ASTM D 2270	174
Total Base Number	mgKOH/g	ASTM D 2896	7.5
Color		ASTM D 1500	<3.0
CCS	cP	ASTM D 5293	5760
HTHS	cP	ASTM D 5481	3.9

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.