



NINJUTSU SHL-T298

Product Description:

NINJUTSU ATF III (H) is a premium quality automatic transmission fluid intended for use as service-fill for automatic transmissions and vehicle components that use automatic transmission fluid as a lubricant or hydraulic fluid, such as transfer cases, manual transmissions and power steering systems. NINJUTSU ATF III (H) has a very high viscosity index and offers resistance against corrosion and foam building. The product also has good anti oxidation and anti wear properties.

Applications / Benefits:

Provides excellent protection against rust and corrosion
Better seal compatibility ensures longer seal life and reduces possibility of oil leakage
Effective foam control leads to smooth & lasting shift feel and reduces Fluid loss
Improved low temperature Fluidity leads to easy pumping in the hydraulic circuits

Specifications, Approvals & Recommendations

GM Dexron IIIH
Ford Mercon
Allison C-4

Typical Physical Characteristics

Test Description	Method	T298
Specific Gravity @15°C	ASTM D 4052	0.853
Flash point, °C	ASTM D 92	198
Pour Point, °C	ASTM D 97	-45
Kinematic Viscosity, @40°C cSt	ASTM D 445	38.1
@100°C cSt	ASTM D 445	7.24
Viscosity Index	ASTM D 2270	157
Appearance	Visual	Red

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.
Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.
Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.