



## NINJUTSU SHL-T299

### Product Description:

Ninjutsu Power Steering Fluid (PSF) delivers increased system life. Designed with Anti-Wear System Protection, Ninjutsu PSF protects against pump failure, squeals and clogs. It contains a seal swell additive to reduce leaks and an anti-shudder additive not found in Automatic Transmission Fluids (ATFs). It can be used to top up select power steering fluids and systems.

### Applications / Benefits:

Foam inhibitors help extend fluid life  
Minimises shudder (noise & chatter) in power steering pumps  
Protects against rust and corrosion  
Seals and helps prevent small leaks  
Superior thermal stability

### Specifications, Approvals & Recommendations

Chrysler MS-1872  
Chrysler MS-5931, P/N 04883077  
Ford M2C 195-A  
GM P/N 89021184  
GM 9985010, P/N 1052884  
Hyundai PSF-3  
Kia PSF-3  
MB 236.3, P/N 000 989 88 03  
Mitsubishi PS Fluid  
Mitsubishi Diamond SP III  
Nissan PSF-II  
Saab P/N (45) 30 09 800  
Subaru P/N K0209A0080  
Toyota PSF Type EH, P/N 008886-01

### Typical Physical Characteristics

| Test Description               | Method      | T299          |
|--------------------------------|-------------|---------------|
| Specific Gravity @15°C         | ASTM D 4052 | 0.858         |
| Flash point, °C                | ASTM D 92   | 202           |
| Pour Point, °C                 | ASTM D 97   | -39           |
| Kinematic Viscosity, @40°C cSt | ASTM D 445  | 36.9          |
| @100°C cSt                     | ASTM D 445  | 6.81          |
| Viscosity Index                | ASTM D 2270 | 145           |
| Appearance                     | Visual      | Red / Neutral |

### Health, Safety & Environment

#### Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

#### Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.