



NINJUTSU SHL-T350, T351, T352

Product Description:

NINJUTSU GEAR OIL LSD is fully synthetic gear oil using the latest technology that ensures superior performance in every area required of differential gears, including LSD (Limited Slip Differential). NINJUTSU GEAR OIL LSD reduces wear and provides cleanliness in extreme conditions. This thermally stable gear lubricant is designed to operate and protect in both high and low extreme temperature conditions.

High performance automotive gear oil. Designed for limited slip differential (LSD) of 4-WD (four-wheel drive) vehicles.

Applications / Benefits:

Very high levels of rust and corrosion resistance
Excellent oxidation stability
Long drain capability
Outstanding low and high temperature performance
Very good thermal stability

Specifications, Approvals & Recommendations

API GL-5
API MT-1
Mack GO-J
Meritor 076-A
Meritor 076-D
Meritor 076-Q
AGMA 9005-E02
Cincinnati Machine
Cleanliness performance in oxidation tests
SAE J2360
MIL-PRF-2105E
PG-2
Ford WSP-M2C197-A
ASIT 224
AGMA 9005-D94
US Steel 224
DIN 51517:3
Limited Slip

Typical Physical Characteristics

Test Description	Method	T350	T351	T352
SAE Viscosity Grade	SAE J 306	75W-85	75W-90	75W-140
Specific Gravity @15°C	ASTM D 4052	0.866	0.868	0.878
Flash point, °C	ASTM D 92	202	206	210
Pour Point, °C	ASTM D 97	-39	-39	-36
Kinematic Viscosity, @40°C cSt	ASTM D 445	70.5	82.1	140.7
@100°C cSt	ASTM D 445	12.5	14.5	24.4
Viscosity Index	ASTM D 2270	178	185	207
Color	ASTM D 1500	<1.5	<1.5	<1.5

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.