



P
R
O
D
U
C
T

BAJUTSU SHL- G306, G307, G308

Product Description:

Bajutsu Synthetic oil is Premium Tier Full SAPS Additive Technology Fulfilling ACEA A3/B4, API SP and OEM Requirements. It delivers excellent wear protection and antioxidant performance, as well as lowspeed pre-ignition (LSPI) protection. It provides robust operation for your vehicle and supports a longer vehicle life. They are designed for a use in high performance gasoline and light duty diesel engines and are typically used in newer vehicles as they provide the minimum performance demanded by many OEM specifications.

Applications / Benefits:

Outstanding oxidation performance
Sludge Handling
Robust LSPI prevention and wear protection
Tailored sludge and varnish control

Specifications, Approvals & Recommendations

API SP
ACEA A3/B4
MB 226.5/229.3
PSA B71 2300 ***
Renault RN 0700 / 0710
VW 501.00 / 505.00

D
A
T
A

Typical Physical Characteristics

Test Description	Method	G306	G307	G308
SAE Viscosity Grade	SAE J 300	5W-30	5W-40	10W-40
Specific Gravity @ 15 °C	ASTM D 4052	0.859	0.860	0.869
Flash Point, °C	ASTM D 92	222	226	220
Pour Point , °C	ASTM D 97	-36	-36	-33
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	11.91	14.52	91.5
cSt @ 100°C	ASTM D 445	71.62	88.10	14.50
Viscosity Index	ASTM D 2270	163	172	165
TBN, mgKOH/g	ASTM D 2896	11.1	11.1	11.0
Color	ASTM D 1500	<3.5	<3.5	<3.5

S
H
E
E
T

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.