

BAJUTSU SHL-G420

Product Description:

Bajutsu Fully Synthetic Motor Oil is designed to provide robust performance in the new industry wear and pre-ignition tests to ensure optimal protection for the latest turbocharged gasoline direct injection (TGDI) and non-TGDI engines. It provides low-speed pre-ignition (LSPI) and timing chain wear protection, improves piston cleanliness and fuel economy.

Bajutsu 0W-8 is engineered for use in select Toyota gasoline and hybrid engines where this viscosity is recommended.

Applications / Benefits:

Excellent cold start properties even at low temperatures of below -35°C
 Exceptional engine protection
 Helps extend engine life by working to prevent damaging deposits and sludge buildup
 High shear stability
 Outstanding fuel saving performance

Specifications, Approvals & Recommendations

API SQ
 JASO GLV-1

Typical Physical Characteristics

Test Description	Unit	Method	Test Results
Appearance	-	Visual	B & C
Color	-	D 1500	<3.5
Density @ 15 °C	kg/l	D 4052	0.8479
Density @ 20 °C	kg/l	D 4052	0.8448
Density @ 30 °C	kg/l	D 4052	0.8385
Kinematic Viscosity @ 40°C	cSt	D 445	25.17
Kinematic Viscosity @ 100°C	cSt	D 445	5.142
Viscosity Index	-	D 2270	138
Total Base Number	mgKOH/g	D 2896	6.9
Flash Point COC	°C	D 92	220
Pour Point	°C	D 97	-45
CCS	cP	D 5293	3988

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.