



P
R
O
D
U
C
T

BATTOJUTSU SHL-A315, A316, A317

Product Description:

Battojutsu Coolant Antifreeze is a colored liquid that is mixed with water to help regulate your engine during extreme temperatures. As the temperature outside changes from hot to cold coolant is pumped throughout the engine block to maintain an even operating temperature. Antifreeze does more than just regulate temperature, however. Maintaining proper fluid levels also helps to prevent corrosion.

Applications / Benefits:

Aids heat transfer
Prevents rust & scales from building up
Protect your engine from corrosion

D
A
T
A

Typical Physical Characteristics

Test Description	Unit	Method	SHL- A315	SHL- A316	SHL- A317
Specific Gravity	@15°C	ASTM D 4052	1.049	1.075	1.082
Freezing Point	°C	ASTM D 1177	-15	-35	-45
Boiling Point	°C	ASTM D 1120	105	108	111
Color			Blue	Blue	Blue

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from your Shinolub representative.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

S
H
E
E
T